

PRODUCT DATA SHEET

Geo-Fix®

ALL WEATHER

Paving Jointing Compound



Ready to use self setting permanent joint filler for use in both dry and wet conditions

FEATURES & BENEFITS

- ✔ Can be used in both dry **and wet** conditions- no more wasted days due to wet weather
- ✔ Can be used on joint widths of a minimum of 5 mm wide and a minimum of 15 mm deep
- ✔ **GEO-FIX®** is unaffected by wind, rain washout and mechanical sweeping equipment
- ✔ No mixing required
- ✔ Brush applied - no special skills or equipment needed
- ✔ Non staining - attractive and neat finish
- ✔ Up to 20 times faster to complete than traditional methods
- ✔ Durable joints which are unaffected by frost, salt UVA and chemicals
- ✔ Resists weed and plant growth between joints
- ✔ Water and air permeable - allows for continued nourishment of tree and plant roots
- ✔ Enables ornate paving patterns and designs to be jointed quickly and effective
- ✔ Comparable strength to 4:1 mortar when set

USES

GEO-FIX® is a quick and easy way of applying a rigid joint over 5mm wide on all types of paving having joint widths of 5mm and over

- ✔ Indian Stone
- ✔ Concrete
- ✔ Slate
- ✔ Clay
- ✔ Terracotta
- ✔ Granite
- ✔ Porcelain

PRODUCT INFORMATION

PACKAGING - GEO-FIX® All Weather is supplied in hermetically sealed 14kg packs.

APPEARANCE / COLOUR - Stone / Mid Grey / Slate Grey / Anthracite / Graphite

JOINT WIDTH - minimum 5 mm

JOINT DEPTH - minimum 15mm

MINIMUM JOINT DEPTH - with light vehicular traffic - 40 mm**

WORKING TEMPERATURE - 3°C to 30°C

WORKABILITY DURATION - *approx 45 minutes

*at 20°C and 50% relative air humidity working time reduces to 30 minutes

YIELD - approx 15m² joint width 6 mm x 15 mm joint depth - 450 mm x 450 mm paving units

SHELF LIFE - GEO-FIX® All Weather has a minimum shelf life of 24 months when stored in unopened packs in accordance with the manufacturers instructions.

STORAGE - Store in a cool dry place out of direct sunlight. Protect the pack from punctures or piercing. Any exposure to air will start the curing process.

On areas subject to occasional light vehicular traffic.

**See details on application procedure for use in such areas

WATCH POINTS

Use GEO-FIX® All Weather within 45 minutes of opening.

* In temperatures exceeding 20°C the material MUST be used within 30 minutes of opening the bag.

Do not use in temperatures below 3°C or if the ground temperature is below 3°C
When applying GEO-FIX® All Weather the paving elements must be kept damp.

HEALTH & SAFETY

***For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.**

May cause sensitization by skin contact. Keep out of the reach of children. Wear suitable gloves. If swallowed seek medical advice and immediately show this product information, packaging or label.

ECOLOGY, HEALTH & SAFETY

For advice and information on the safe handling, storage and disposal of the product, users should refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

The following general comments apply to all products.

SOLVENT BASED PRODUCTS

Use in well-ventilated areas avoiding inhaling. Suitable respiratory Equipment may be needed, e.g.. when spraying. Can cause skin, eye irritation. Wear protective eye shields and gloves during use. Do not smoke or allow sparks or naked lights when stored or in use.

POWDER PRODUCTS

Should be handled to minimize dust formation; use light mask if excessive dust is unavoidable

RESIN PRODUCTS

Can cause irritation, dermatitis or allergic reaction. Use protective equipment particularly for skin and eyes. Use only in well ventilated areas.

SPILLAGE

Chemical products can cause damage; clean spillage immediately.

LEGAL NOTES

The information given here is given in good faith, based on our best knowledge and experience of the products not only on laboratory work but also on field experience when properly stored, handled and applied under normal conditions in accordance with Geofix's recommendations. However, due to numerous factors affecting results the user of the product must test the product's suitability for the intended application and purpose. We offer this information without any guarantee and no patent liability is assumed.

For additional information or questions, please contact our technical department.